

DECLARATION OF PERFORMANCE

No: **DoP-Whiting - EN12620 – 09/14**

Issue date: 01st June 18

- | | | |
|---|---------------------------------|---|
| 1 | Identification code of product: | Limestone Fine Whiting |
| 2 | Type, batch or serial number: | Whiting <i>dd/mm/yyyy</i> # # # |
| 3 | Intended use: | Filler aggregate for concrete and mortar |
| 4 | Manufacturer: | Kilwaughter Minerals Ltd
9 Starbog Road
Larne
BT40 2TJ

Phone: 028 2826 0766
Web: www.kilwaughter.com |
| 5 | Authorised representative | N/A |
| 6 | System of assessment | Conforms to Annex ZA of EN 12620:2013 Attestation System 4
Factory production control is in accordance with Annex H and monitored in compliance with an EN ISO9001 Quality Management System
(BSI certificate No FM 85394). |
| 7 | Declaration of performance: | |

Essential Characteristic	Performance	Harmonised Standard								
Particle Size:	Category Filler Aggregate <table border="0" style="margin: auto;"> <tr> <td style="text-align: left;">Sieve Size</td> <td style="text-align: left;">Typical Grading (% Passing)</td> </tr> <tr> <td>2.0 mm</td> <td>100</td> </tr> <tr> <td>0.125 mm</td> <td>85 to 100</td> </tr> <tr> <td>0.063 mm</td> <td>70 to 100</td> </tr> </table>	Sieve Size	Typical Grading (% Passing)	2.0 mm	100	0.125 mm	85 to 100	0.063 mm	70 to 100	EN12620:2013
Sieve Size	Typical Grading (% Passing)									
2.0 mm	100									
0.125 mm	85 to 100									
0.063 mm	70 to 100									
Particle Density: Loose bulk density in Kerosene(EN1097-7):	2.70 Mg/m ³ 0.8 Mg/m ³									
Composition/Content;	Chloride <0.01% Acid soluble sulphate AS _{0.2} Total sulphur 0.20 %									
Cleanliness:	NPD									
Volume stability:	NPD									
Release of other dangerous substances	NPD									


Statement

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Neil Bareham
QA Manager

Date
Place of Issue


01 st June 18
Larne, Co Antrim, UK



Kilwaughter Minerals Ltd
 9 Starbog Road
 Larne
 Northern Ireland
 BT40 2TJ

Limestone Fine Whiting

EN 12620:2013

Aggregates for concrete

Fineness/Particle Size	>70% passing 63µm
Particle Density	2.70 Mg/m ³
Composition/Content	
Chloride	<0.01%
Acid soluble sulphate	AS _{0.2}
Total sulphur	0.20 %
Cleanliness	NPD
Volume stability	
Drying Shrinkage	NPD
Release of other dangerous substances	NPD